

HONDA

MARINE



**Premium Power.
Unparalleled Performance.
Extraordinary Experiences.**

The All-New
Honda
BF350 V8

Distributed by Victormax Sdn Bhd

Engine Technical Specifications

| | BF15 | BF60 / BFP60 | BF90 | BF100 |
|-------------------------------|--|---|--|---|
| Type | 4-Stroke SOHC 2 Cylinder/4 Valves | 4-Stroke SOHC 3 Cylinder / 12 Valves | 4-Stroke SOHC 4 Cylinder / 16 Valves | 4-Stroke SOHC 4 Cylinder / 16 Valves |
| Displacement | 350 cc (21.5 cubic inches) | 988 cc (61.0 cubic inches) | 1,496 cc (91.4 cubic inches) | 1,496 cc (91.4 cubic inches) |
| Bore & Stroke | 59mm x 64mm (2.3 x 2.5 inches) | 73 mm x 79.5 mm (2.9 x 3.1 inches) | 73 mm x 89.4 mm (3.0 x 3.5 inches) | 73 mm x 89.4 mm (3.0 x 3.5 inches) |
| Full Throttle RPM Range | 4,500 - 5,500 RPM | 5,000 - 6,000 RPM | 5,300 - 6,300 RPM | 5,300 - 6,300 RPM |
| Rated Power | 15 HP @ 5,000 RPM | 60 HP @ 5,500 RPM | 90 HP @ 5,800 RPM | 100 HP @ 5,900 RPM |
| Cooling System | Water Cooled | Water Cooled | Water Cooled | Water Cooled |
| Fuel Delivery | 1 Carburetor | Programmed Fuel Injection | PGM-FI VTEC | PGM-FI VTEC |
| Starting System | Electric/Recoil | Electric | Electric | Electric |
| Exhaust | Through Hub | Through Hub | Through Hub | Through Hub |
| Drive | | | | |
| Gear Ratio | 2.08:1 | 2.07:1 / 2.33:1 | 2.33:1 | 2.33:1 |
| Gear Oil Capacity | 0.285L | 0.43L / 0.95L | 0.95L | 0.95L |
| Gear Shift | F-N-R | F-N-R | F-N-R | F-N-R |
| Alternator (Electric Start) | 6 Amp | 22 Amp | 44 Amp | 44 Amp |
| Power Trim & Tilt | - | Standard | Standard | Standard |
| Propeller | 4-Blade Aluminum | Aluminium | Stainless Steel | Stainless Steel |
| Recommended Transom Height | (S) 381mm / 15 in. (L) 508mm / 20 in. | (L) 521mm / 20 in. | (L) 508mm / 20 in. (X) 635mm / 25 in. | (X) 635mm / 25 in. |
| Dry Weight | (S) 47kg / 104 lbs. (L) 50kg / 110 lbs. | (L) 108kg / 239 lbs. | (L) 163kg / 359 lbs. (X) 166kg / 365 lbs. | (X) 166kg / 365 lbs. |

| | BF115 | BF150 | BF200 | BF250 |
|-------------------------------|---|---|-------------------------------------|--|
| Type | 4-Stroke DOHC 4 Cylinder / 16 Valves | 4-Stroke DOHC 4 Cylinder / 16 Valves | 4-Stroke, SOHC 60° V6, 24 Valve | 4-Stroke, SOHC 60° V6, 24 Valve |
| Displacement | 2,354 cc (144 cubic inches) | 2,354 cc (144 cubic inches) | 3,583 cc (219 cubic inches) | 3,583 cc (219 cubic inches) |
| Bore & Stroke | 87 mm x 99 mm (3.43 x 3.9 inches) | 87 mm x 99 mm (3.43 x 3.9 inches) | 89 mm x 96 mm (3.5 x 3.8 inches) | 89 mm x 96 mm (3.5 x 3.8 inches) |
| Full Throttle RPM Range | 4,500 - 6,000 RPM | 5,000 - 6,000 RPM | 5,000 - 6,000 RPM | 5,300 - 6,300 RPM |
| Rated Power | 115 HP @ 5,250 RPM | 150 HP @ 5,500 RPM | 200 HP @ 5,500 RPM | 250 HP @ 5,800 RPM |
| Cooling System | Water Cooled | Water Cooled | Water Cooled | Water Cooled |
| Fuel Delivery | Programmed Fuel Injection | PGM-FI VTEC | Programmed Fuel Injection | PGM-FI VTEC |
| Starting System | Electric | Electric | Electric | Electric |
| Exhaust | Through Hub | Through Hub | Through Hub | Through Hub |
| Drive | | | | |
| Gear Ratio | 2.14:1 | 2.14:1 | 2.00:1 | 2.00:1 |
| Gear Oil Capacity | 0.98L | 0.98L | 1.47L | 1.47L |
| Gear Shift | F-N-R | F-N-R | F-N-R | F-N-R |
| Alternator (Electric Start) | 55 Amp | 51 Amp | 90 Amp | 90 Amp |
| Power Trim & Tilt | Standard | Standard | Standard | Standard |
| Propeller | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel |
| Recommended Transom Height | (X) 635mm / 25 in. | (X) 635mm / 25 in. | (X) 635mm / 25 in. | (X) 635mm / 25 in. (U) 762mm / 30 in. |
| Dry Weight | (X) 220kg / 485 lbs. | (X) 220kg / 485 lbs. | (X) 278kg / 613 lbs. | (X) 280kg / 617 lbs. (U) 285kg / 628 lbs. |



BF15



BF60



BF90



BF100



BF115



BF150



BF200



BF250

BF300 & BF350 Specifications

| Engine | | BF300 / BF350 |
|----------------------------|--------|---------------------------------------|
| Engine Type | | 4-Stroke SOHC 8-Cylinder/32 Valves |
| Displacement | | 4952 cc (302 cubic in.) |
| Bore & Stroke | | 89 x 99.5 mm (3.5 x 3.9 in.) |
| Compression Ratio | | 10:1 |
| Full Throttle RPM Range | | 5000-6000 RPM |
| Rated Power | | 300 HP @ 5500 RPM / 350 HP @ 5500 RPM |
| Cooling System | | Water Cooled |
| Fuel Delivery | | Programmed Fuel Injection |
| Ignition System | | Micro-Computer Programmed |
| Starting System/Alternator | | Electric/93 Amps Total |
| Battery Charging Power | | 70 Amps |
| Exhaust | | Through Hub |
| Lubrication | | Wet Sump |
| Trim Range | | -4° to +15° |
| Tilt Range | | 68° |
| Octane | | 86 |
| Idling Engine Speed Range | | 650 + 50 RPM |
| Trolling Mode Range | | 650-1000 RPM |
| Cruise Control Range | | 650-6000 RPM |
| Drive System | | |
| Gear Ratio | | 1.79:1 |
| Dimensions | | |
| Overall Width (mm/in.) | | 650 mm/25.6 in. |
| Recommended | X-Type | 635 mm/25 in. |
| Transom Height | U-Type | 762 mm/30 in. |
| Dry Weight | X-Type | 347 kg/765 lbs. |
| | U-Type | 352 kg/776 lbs. |
| Equipment | | |
| Propeller | | Optional |



The Honda BF350 V8 is available in Aquamarine Silver or Grand Prix White.

Accessories

Standard accessories



Tachometer



Hours Meter



Side-Mount Remote Control

Optional add-ons



Top-Mount Remote Control



Top-Mount Key Switch with Emergency Stop



Panel Indicators



Multifunction Tiller Handle with Indicators



Speedometer

DBW (Drive by Wire) Accessories



Top-Mount DBW Remote Control



On-off Switch



Display Kit



Multi Trim Switch



On Off Switch with Emergency Stop



7inch Display Kit

Oils & Lubricants



Honda Marine 10W-30 Engine Oil



VM-TEC 10W-40 Premium Engine Oil



VM-TEC 20W-50 Premium Engine Oil



VM-TEC SAE 90 GL-5 Premium Gear Lube

Authorised Dealer / Branch:

Blank area for dealer information.